

Refraksiya ish stansiyasi COS-6100/3100



- To'liq funksional paketlar
- Optimallashtirilgan kombinatsiyalar
- Xavfsizlik mexanizmlari motorli stol
- Sinalgan mustahkam konstruksiya
- Moslashtiriladigan qo'shimcha aksessuarlar

Texnik xususiyatlari

COS-6100 stoli (ST-6100)

RT tayanchi (qo'li)	Elektromagnit qulf
RT tayanchining yuqoriga-pastga harakati	Yo'li 310 mm
RT tayanchining oldinga-orqaga harakati	Bemor tomonga yo'li 230 mm
Quvvat manbai	AC 100–120 V / AC 220–240 V, 50/60 Gts
Quvvat sarfi	600 VA (maksimal, RT va boshqa optometriya qurilmalari bilan)
Standart aksessuarlar	Quvvat kabeli, saqlagich, jadval uchun quvvat kabeli, refraktor kallagini osish kronshteyni
Qo'shimcha aksessuarlar	O'ng yon stol, chap yon stol, ikki qurilmali o'rnatish to'plami (o'ng), ikki qurilmali o'rnatish to'plami (chap), o'tkazish kabeli (OPD-Scan III ni o'rnatish uchun), Takagi shchel lampasi uchun bir qurilmali o'rnatish to'plami, MEM-200 o'rnatish to'plami, SL-1800 o'rnatish to'plami (ikki qurilmali laganda uchun), SL-1800 o'rnatish to'plami (bir qurilmali laganda uchun), AR-F/ARK-F o'rnatish plastinasi, OPD-Scan III o'rnatish plastinasi (ikki qurilmali laganda uchun), qo'lda RT o'rnatish to'plami (o'ng), qo'lda RT o'rnatish to'plami (chap), CP3B-19 to'plami, sinov linzalari uchun laganda

Refraktor RT-6100

Sfera	-29.00 dan +26.75 D gacha (0.12/0.25/0.50 dan 3.00 D gacha qadam); -19.00 dan +16.50 D gacha (kross-silindr testi, prizma testi)
Silindr	0.00 dan ± 8.75 D gacha (0.25/1.00/2.00/3.00 D qadam)
O'q	0 dan 180° gacha (1°/5°/15° qadam)
PD (ko'zlararo masofa)	48 dan 80 mm gacha (uzoq rejim); 50 dan 74 mm gacha (yaqin ish masofasi 35 sm); 54 dan 80 mm gacha (100% konvergensiya uchun uzoq PD mumkin)
Prizma	0.00 dan 20.00Δ gacha (0.1/0.5/2Δ qadam)
Kross-silindr linza	± 0.25 , ± 0.50 , ± 0.25 D avto-kross
Okkluder	Mavjud
Teshikli plastina (pinhole)	ø2.0 mm

Qizil/yashil filtr	O'ng ko'z: qizil, chap ko'z: yashil
PD tekshirish linzasi	Mavjud
Polyarizatsion filtrlar	O'ng ko'z: 135° / chap ko'z: 45°, o'ng ko'z: 45° / chap ko'z: 135°
Mahkamlangan kross-silindr linza	±0.50 D (o'q 90° ga o'rnatilgan holda mahkamlangan)
Retinoskop uchun sferik linzalar	0/+1.5/+2.0 D (sozlama orqali tanlanadi)
Qizil Maddoks tayoqchasi	O'ng ko'z: gorizontal, chap ko'z: vertikal
Dissotsiatsiya prizmasi	O'ng ko'z: 6ΔBU / chap ko'z: 10ΔBI
Binokulyar ochiq tumanlash (fogging)	0.00 dan +9.00 D gacha
Ko'rish maydoni	40° (VD = 12 mm), 39° (VD = 13.75 mm)
Yaqin ko'rish uchun refraksiya masofasi	350 dan 700 mm gacha (50 mm qadam)
Peshona tayanchini sozlash	25 ±2 mm
Display	10.4 dyuymli rangli LCD
Printer	Yuqori tezlikli chiziqli printer
Interfeys	RS-232C: 1 ta port (jadval ko'rsatish qurilmasini ulash uchun); USB: 1 ta port; LAN: 3 ta port; simsiz LAN (WLAN): ixtiyoriy (faqat radio qonuni bo'yicha sertifikatlangan mamlakatlar (hududlar) uchun)
Quvvat manbai	AC 100–240 V, 50/60 Gts
Quvvat sarfi	90 VA
O'lchamlari/massasi: refraktor kallagi	408(K) x 107(Ch) x 277(B) mm / 3.2 kg (16.1 x 4.2 x 10.9" / 7.1 lbs.)
O'lchamlari/massasi: boshqaruv pulti	260(K) x 230(Ch) x 207(B) mm / 2.1 kg (10.2 x 9.1 x 8.1" / 4.6 lbs.)
O'lchamlari/massasi: oraliq blok	189(K) x 221(Ch) x 73(B) mm / 1.4 kg (7.4 x 8.7 x 2.9" / 3.1 lbs.)
O'lchamlari/massasi: printer	101(K) x 86(Ch) x 121(B) mm / 0.6 kg (4.0 x 3.4 x 4.8" / 1.3 lbs.)
Standart aksessuarlar (RT-6100)	Yuz himoyasi, peshona tayanchi, stilus qalam, printer qog'ozi, chang qopqog'i, yaqin nuqta jadvali, yaqin nuqta tayoqchasi, dasta, quvvat kabeli, aloqa kabeli
Qo'shimcha aksessuarlar (RT-6100)	Eye Care kartasi, infraqizil aloqa bloki, refraktor kallagini egish bloki, boshqaruv pulti tayanchi, simsiz LAN moduli, Memory box, Space Saving Chart SSC-100, yaqin nuqta tayoqchasi, oraliq blok — boshqaruv pulti kabeli 10 m, LAN kabeli, RT-6100 CB for Windows

Ishlab chiqaruvchi: NIDEK CO., LTD. (Yaponiya) — www.nidek-intl.com

To'liq katalog va narx so'rash: medkatalog.vercel.app