

Mikroperimetr MP-3



- Keng o'lchash diapazonli mikroperimetriya
- Aniq kuzatuv tizimli fiksatsiya testi
- Yuqori ruxsatli midriazsiz fundus-kamera
- Ko'rishni tiklash uchun teskari aloqali tekshiruv
- Skotopik mikroperimetriya
- Avtomatik kuzatuv va avtomatik tekislash

Texnik xususiyatlari

Mikroperimetriya

Ko'rish maydoni	40°
Maksimal stimul yorqinligi	10 000 asb (ISO12866 o'lchash usullariga muvofiq)
Fon yorqinligi	31.4 asb / 4 asb (ISO12866 ga muvofiq); skotopik mikroperimetriya testi (faqat MP-3 type S): 0.003 asb
Stimul yorqinligi bo'sag'a diapazoni	Standart [fon 31.4 asb]: 10 031.4 asb (0 dB) dan 35.4 asb (34 dB) gacha (kontrast 319.5 dan 0.13 gacha); NIDEK MP-1 ga ekvivalent [fon 4 asb]: 404 asb (0 dB) dan 8 asb (20 dB) gacha (kontrast 101 dan 1.01 gacha), 1 004 asb (0 dB) dan 4.4 asb (34 dB) gacha (kontrast 251 dan 0.1 gacha); skotopik [fon 0.003 asb]: 0.303 asb (0 dB) dan 0.0042 asb (24 dB) gacha (kontrast 101 dan 0.4 gacha)
Stimul o'lchami	Goldman I/II/III/IV/V ga mos
Bo'sag'a strategiyasi	4-2 / 4-2-1
Fiksatsiya nishoni	Shakli: bitta xoch, doira, to'rtta xoch, to'rtta chiziq; rangi: oq/sariq/qizil/ko'k dan tanlanadi

Fundus-kamera

Turi	Midriazsiz fundus-kamera, rangli
Ko'rish burchagi	45° ±5% (ko'z refraksiyasi 0 D)
Eng kichik qorachiq diametri	ø4 mm
Kamera	O'rnatilgan 12 megapikselli CCD kamera
Avtomatik kuzatuv	X-Y-Z yo'nalishlarda
Avtomatik suratga olish	Mavjud
Ish masofasi	45.7 mm
Display	10.4 dyuymli rangli LCD sensorli ekran
Dioptriya korreksiyasi diapazoni	-25 dan +15 D gacha
Ko'z tubi avtofokus diapazoni	-12 dan +15 D gacha
Quvvat manbai	AC 100–240 V, 50/60 Gts

Quvvat sarfi	160 VA
O'lchamlari/massasi	334(K) x 562(Ch) x 560(B) mm / 36 kg (13.1 x 22.1 x 22.0" / 79 lbs.)
Qo'shimcha aksessuarlar	Motorli optik stol

Ishlab chiqaruvchi: NIDEK CO., LTD. (Yaponiya) — www.nidek-intl.com
To'liq katalog va narx so'rash: medkatalog.vercel.app