

Tizimli linza ishlov berish stanogi MSE-1



- Yuqori tezlik va yuqori aniqlik
- Keng ishlov berish imkoniyatlari
- Optimal natija uchun yuqori unumdor konstruktsiya
- Laboratoriya ham, savdo nuqtasi ham uchun ideal

Texnik xususiyatlari

Ishlov berish tizimi	Shablonsiz (patternless)
Rejim	Faska (bevel) hosil qilish; mini-faska (0.4 dan 0.7 mm gacha) (0.1 mm qadam); yuqori baza egriligi uchun faska; maxsus (custom) faska; pog'onali (step) faska; qisman pog'onali faska; tekis ishlov (flat edging); ariqcha ochish (grooving); silliqlash (polishing); chamfer (silliqlangan chamfer ixtiyoriy); dizayn kesish (design cut); teshik ochish (drilling); yumshoq ishlov (soft processing)
Suv ta'minoti tizimi	Nasos orqali aylanma yoki to'g'ridan-to'g'ri suv quvuriga ulanish
Interfeys	RS-232C: 3 ta port; LAN: 1 ta port; USB: 1 ta port
Quvvat manbai	AC 100–120 V / AC 200–240 V, 50/60 Gts
Quvvat sarfi	1.5 kVA
Havo: muhit / bosim / sarfi	Quruq havo / 0.3 dan 0.35 MPa gacha / 35 l/min; kompressor (mijoz tomonidan ta'minlanadi) uzluksiz ishlashga qodir bo'lishi kerak (havo sarfi: 70 l/min va undan yuqori)
O'lchamlari/massasi	700(K) x 570(Ch) x 670(B) mm (separatorsiz) / 80 kg (separator bilan) (27.6 x 22.4 x 26.3" / 176 lbs.)
Standart aksessuarlar	Pardozlash g'ildiragini tuzatish tayoqchasi, silliqlash g'ildiragi uchun pasta to'plami, kalibrlash moslamasi, stilus qalam, kalit, shpindel kaliti, tekis linza, olti qirrali otvyorka, parma, dag'al ishlov asbobi, dag'al asbobni almashtirish moslamasi, moslashuvchan kosacha, yuqori baza egriligi uchun moslashuvchan kosacha, kosachani olgich, ikki tomonlama yelimli yostiqcha, sim bog'ich, aksessuarlar qutisi, ferrit o'zak, akustik gilamcha, uzaytirgich kabel (2 dona), quvvat kabeli
Qo'shimcha aksessuarlar	Shtrix-kod skaneri, aylanma nasos baki, USB flesh-disk, MSE-1 uchun stol, xavfsiz faskani silliqlash g'ildiragi, regulyator to'plami, WECO linza adapteri, parma (Ø1.0, 1.2, 1.6)

Sozlash diapazoni

FPD (oprava markazlari masofasi)	30.00 dan 99.50 mm gacha (0.01 mm qadam)
PD (ko'zlararo masofa)	30.00 dan 99.50 mm gacha (0.01 mm qadam)
1/2PD	15.00 dan 49.75 mm gacha (0.01 mm qadam)
Optik markaz balandligi	±15.0 mm (0.1 mm qadam)

O'lchamni sozlash	±9.95 mm (0.01 mm qadam)
-------------------	--------------------------

Eng kichik ishlov o'lchami

Tekis ishlov	ø32.0 x 19.0 mm
Faska bilan ishlov	ø33.6 x 20.6 mm
Xavfsiz faska (tekis)	ø34.0 x 21.0 mm
Xavfsiz faska (faskali)	ø35.6 x 22.6 mm
Yuqori baza egriligi uchun faska (faska balandligi 0.8 mm uchun)	ø37.9 x 24.4 mm
Ariqcha ochish	ø32.0 x 19.0 mm

Teshik ochish (drilling)

Teshik diametri	ø0.80 dan 10.00 mm gacha (0.01 mm qadam)
Teshik chuqurligi	0.1 dan 6.0 mm gacha
Teshik ochish uchun eng kichik linza diametri	7° dan kam: ø34.0 mm; 7° va undan katta: ø30.0 mm
Teshik ochish yo'nalishi	Avtomatik/qo'lda og'dirish 0 dan 30° gacha

Ishlab chiqaruvchi: NIDEK CO., LTD. (Yaponiya) — www.nidek-intl.com

To'liq katalog va narx so'rash: medkatalog.vercel.app