

Intellektual refraktor RT-3100



- Linzalarni silliq, tez va shovqinsiz tanlash
- Tushunarli rangli LCD sensorli ekran
- Aniq oq LED yoritish
- Yuqori sifatli yaqin nuqta kartasi

Texnik xususiyatlari

O'lchash diapazoni

Sfera	-19.00 dan +16.75 D gacha (0.25/0.50 dan 3.00 D gacha qadam)
Silindr	0.00 dan ± 6.00 D gacha (0.25/1.00 D qadam)
O'q	0 dan 180° gacha (1°/5° qadam)
PD (ko'zlararo masofa)	48 dan 80 mm gacha (uzoq rejim); 50 dan 74 mm gacha (yaqin ish masofasi 35 sm); 54 dan 80 mm gacha (100% konvergensiya uchun uzoq PD mumkin)
Prizma	0.00 dan 20.00 Δ gacha (0.10/0.50/2.00 Δ qadam)

Yordamchi linzalar

Kross-silindr linza	± 0.25 D
Okkluder	Mavjud
Teshikli plastina (pinhole)	$\varnothing 2.0$ mm
Qizil/yashil filtr	O'ng ko'z: qizil, chap ko'z: yashil
PD tekshirish linzasi	Mavjud
Polyarizatsion filtrlar	O'ng ko'z: 135° / chap ko'z: 45°, o'ng ko'z: 45° / chap ko'z: 135°
Mahkamlangan kross-silindr linza	± 0.50 D (o'q 90° ga o'rnatilgan holda mahkamlangan)
Retinoskop uchun sferik linzalar	+1.5/+2.0 D (sozlama orqali tanlanadi)
Qizil Maddoks tayoqchasi	O'ng ko'z: gorizonta, chap ko'z: vertikal
Dissotsiatsiya prizmasi	O'ng ko'z: 6 Δ BU / chap ko'z: 10 Δ BI, o'ng ko'z: 3 Δ BD / chap ko'z: 3 Δ BU

Ko'rish maydoni	40° (VD = 12 mm), 39° (VD = 13.75 mm)
Yaqin ko'rish uchun refraksiya masofasi	350 dan 700 mm gacha (50 mm qadam)
Peshona tayanchini sozlash	14 $\pm$ 2 mm
Vertex masofasi belgisi	12, 13.75, 16, 18, 20 mm
Gorizontallikni sozlash	$\pm 2.5^\circ$
Display	5.7 dyuimli rangli LCD

Printer	Yuqori tezlikli chiziqli printer
Interfeys	RS-232C: 2 ta port (1 ta port jadval ko'rsatish qurilmasini ulash uchun, 1 ta port avtorefraktometr yoki kompyuterni ulash uchun)
Quvvat manbai	AC 100–240 V, 50/60 Gts
Quvvat sarfi	80 VA
Standart aksessuarlar	Yaqin nuqta kartasi, yaqin nuqta tayoqchasi, peshona tayanchi, yuz himoyasi, stilus qalam, chang qopqog'i, aloqa kabeli, printer qog'ozi, quvvat kabeli, olti qirrali kalit
Qo'shimcha aksessuarlar	Eye Care kartasi, Memory Box, polyarizatsiyani almashtirish bloki, refraktor kallagini egish bloki, Space Saving Chart SSC-100

O'lchamlari/massasi

Refraktor kallagi	355(K) x 100(Ch) x 276(B) mm / 3.5 kg (14.0 x 3.9 x 10.9" / 7.7 lbs.)
Boshqaruv bloki	160(K) x 209(Ch) x 165(B) mm / 1.7 kg (6.3 x 8.2 x 6.5" / 3.7 lbs.)
Oraliq blok (relay box)	194(K) x 227(Ch) x 61(B) mm / 2.0 kg (7.6 x 8.9 x 2.4" / 4.4 lbs.)

Ishlab chiqaruvchi: NIDEK CO., LTD. (Yaponiya) — www.nidek-intl.com

To'liq katalog va narx so'rash: medkatalog.vercel.app